



**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

- 1.1 Product identifier:** TEKINJECT PU 1C FAST FLEX
PU-10
- Other means of identification:**
Not relevant
- 1.2 Relevant identified uses of the substance or mixture and uses advised against:**
Relevant uses: Water sealing for concrete (Polyurethane). For professional users only.
Uses advised against: All uses not specified in this section or in section 7.3
- 1.3 Details of the supplier of the safety data sheet:**
Tekinject bv
Kruisblok 6
2320 Hoogstraten - Antwerpen - België
Phone: +3237072160
SDSdepartment@tekinject.com
www.tekinject.com
- 1.4 Emergency telephone number:** Tekinject +32 3 707 21 60 Monday till Thursday 08h00 till 16h45, Friday 08h00 till 15h30

SECTION 2: HAZARDS IDENTIFICATION

- 2.1 Classification of the substance or mixture:**
- CLP Regulation (EC) No 1272/2008:**
Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.
Acute Tox. 4: Acute inhalation toxicity, Category 4, H332
Carc. 2: Carcinogenicity, Category 2, H351
Eye Irrit. 2: Eye irritation, Category 2, H319
Resp. Sens. 1: Sensitisation, respiratory, Category 1, H334
Skin Irrit. 2: Skin irritation, Category 2, H315
Skin Sens. 1: Sensitisation, skin, Category 1, H317
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2 (Inhalation), H373
STOT RE 2: Specific target organ toxicity — Repeated exposure, Hazard Category 2, H373
STOT SE 3: Respiratory tract toxicity, single exposure, Category 3, H335
- 2.2 Label elements:**
- CLP Regulation (EC) No 1272/2008:**
Danger
- 

- Hazard statements:**
Acute Tox. 4: H332 - Harmful if inhaled.
Carc. 2: H351 - Suspected of causing cancer.
Eye Irrit. 2: H319 - Causes serious eye irritation.
Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.
Skin Irrit. 2: H315 - Causes skin irritation.
Skin Sens. 1: H317 - May cause an allergic skin reaction.
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).
STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.
STOT SE 3: H335 - May cause respiratory irritation.
- Precautionary statements:**

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 2: HAZARDS IDENTIFICATION (continued)

P201: Obtain special instructions before use.
 P280: Wear protective gloves/face protection/protective clothing/respiratory protection/protective footwear.
 P302+P352: IF ON SKIN: Wash with plenty of water.
 P304+P340: IF INHALED: Remove person to fresh air and keep comfortable for breathing.
 P305+P351+P338: IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
 P308+P313: IF exposed or concerned: Get medical advice/attention.
 P342+P311: If experiencing respiratory symptoms: Call a POISON CENTER or doctor/physician.
 P501: Dispose of contents/container in accordance with regulations on hazardous waste or packaging and packaging waste respectively.

Supplementary information:

EUH204: Contains isocyanates. May produce an allergic reaction.

Substances that contribute to the classification

4,4'-methylenediphenyl diisocyanate, isomers and homologues; Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate; 4,4'-methylenediphenyl diisocyanate

Additional Labelling:

As from 24 August 2023 adequate training is required before industrial or professional use.

2.3 Other hazards:

Product does not meet PBT/vPvB criteria
 Endocrine-disrupting properties: The product does not meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Polyurethane resin

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Identification	Chemical name/Classification	Concentration
CAS: 9016-87-9 EC: 618-498-9 Index: Non-applicable REACH: Non-applicable	4,4'-methylenediphenyl diisocyanate, isomers and homologues⁽¹⁾ Self-classified Regulation 1272/2008 Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger	10 - <25 %
CAS: Non-applicable EC: 905-806-4 Index: Non-applicable REACH: 01-2119457015-45-XXXX	Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate⁽¹⁾ Self-classified Regulation 1272/2008 Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger	10 - <25 %
CAS: 6425-39-4 EC: 229-194-7 Index: Non-applicable REACH: 01-2119969278-20-XXXX	2,2'-dimorpholinyl-diethyl ether⁽¹⁾ Self-classified Regulation 1272/2008 Eye Irrit. 2: H319 - Warning	1 - <2,5 %
CAS: 101-68-8 EC: 202-966-0 Index: 615-005-00-9 REACH: 01-2119457014-47-XXXX	4,4'-methylenediphenyl diisocyanate⁽¹⁾ ATP CLP00 Regulation 1272/2008 Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger	1 - <2,5 %
CAS: 25686-28-6 EC: 500-040-3 Index: Non-applicable REACH: 01-2119457013-49-XXXX	4,4'-Methylenediphenyl diisocyanate, oligomers⁽¹⁾ Self-classified Regulation 1272/2008 Acute Tox. 4: H332; Carc. 2: H351; Eye Irrit. 2: H319; Resp. Sens. 1: H334; Skin Irrit. 2: H315; Skin Sens. 1: H317; STOT RE 2: H373; STOT SE 3: H335 - Danger	<1 %

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

Identification	Specific concentration limit
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319 % (w/w) >=0,1: Resp. Sens. 1 - H334 % (w/w) >=5: STOT SE 3 - H335
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate CAS: Non-applicable EC: 905-806-4	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319 % (w/w) >=0,1: Resp. Sens. 1 - H334 % (w/w) >=5: STOT SE 3 - H335
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	% (w/w) >=5: Skin Irrit. 2 - H315 % (w/w) >=5: Eye Irrit. 2 - H319 % (w/w) >=0,1: Resp. Sens. 1 - H334 % (w/w) >=5: STOT SE 3 - H335

Acute toxicity estimate for the substance in Part 3 of Annex VI to Regulation (EC) No 1272/2008 or as determined in accordance with Annex I to that Regulation:

Identification	Acute toxicity		Genus
	LD50 oral	LD50 dermal	
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	LD50 oral	Not relevant	
	LD50 dermal	Not relevant	
	LC50 inhalation	11 mg/L (ATEi)	
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate CAS: Non-applicable EC: 905-806-4	LD50 oral	Not relevant	
	LD50 dermal	Not relevant	
	LC50 inhalation	11 mg/L (ATEi)	
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	LD50 oral	Not relevant	
	LD50 dermal	Not relevant	
	LC50 inhalation	11 mg/L (ATEi)	

SECTION 4: FIRST AID MEASURES

4.1 Description of first aid measures:

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

Remove the person affected from the area of exposure, provide with fresh air and keep at rest. In serious cases such as cardiorespiratory failure, artificial resuscitation techniques will be necessary (mouth to mouth resuscitation, cardiac massage, oxygen supply, etc.) requiring immediate medical assistance.

By skin contact:

Remove contaminated clothing and footwear, rinse skin or shower the person affected if appropriate with plenty of cold water and neutral soap. In serious cases see a doctor. If the product causes burns or freezing, clothing should not be removed as this could worsen the injury caused if it is stuck to the skin. If blisters form on the skin, these should never be burst as this will increase the risk of infection.

By eye contact:

Rinse eyes thoroughly with lukewarm water for at least 15 minutes. Do not allow the person affected to rub or close their eyes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case this could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS of the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Not relevant

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 5: FIREFIGHTING MEASURES (continued)

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, handling and use. In the case of combustion as a result of improper handling, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

Non-applicable

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Personal protection equipment must be used against potential contact with the spilled product (See section 8). Evacuate the area and keep out those who do not have protection.

For emergency responders:

Wear protective equipment. Keep unprotected persons away. See section 8.

6.2 Environmental precautions:

This product is not classified as hazardous to the environment. Keep product away from drains, surface and ground water.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks. Keep containers hermetically sealed. Control spills and residues, destroying them with safe methods (section 6). Avoid leakages from the container. Maintain order and cleanliness where dangerous products are used.

B.- Technical recommendations for the prevention of fires and explosions

Product is non-flammable under normal conditions of storage, handling and use. It is recommended to transfer at slow speeds to avoid the generation of electrostatic charges that can affect flammable products. Consult section 10 for information on conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

It is recommended to have absorbent material available at close proximity to the product (See subsection 6.3)

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 7: HANDLING AND STORAGE (continued)

7.2 Conditions for safe storage, including any incompatibilities:

A.- Specific storage requirements

- Minimum Temp.: 10 °C
- Maximum Temp.: 30 °C
- Maximum time: 24 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):

There are no applicable occupational exposure limits for the substances contained in the product

DNEL (Workers):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,1 mg/m ³	Not relevant	0,05 mg/m ³
Reaction mass of 4,4'- methylenediphenyl diisocyanate and o-(p- isocyanatobenzyl)phenyl isocyanate CAS: Non-applicable EC: 905-806-4	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,1 mg/m ³	Not relevant	0,05 mg/m ³
2,2'-dimorpholinyldiethyl ether CAS: 6425-39-4 EC: 229-194-7	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	1 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	7,28 mg/m ³	Not relevant
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,1 mg/m ³	Not relevant	0,05 mg/m ³
4,4'-Methylenediphenyl diisocyanate, oligomers CAS: 25686-28-6 EC: 500-040-3	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,1 mg/m ³	Not relevant	0,05 mg/m ³

DNEL (General population):

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,05 mg/m ³	Not relevant	0,025 mg/m ³
Reaction mass of 4,4'- methylenediphenyl diisocyanate and o-(p- isocyanatobenzyl)phenyl isocyanate CAS: Non-applicable EC: 905-806-4	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,05 mg/m ³	Not relevant	0,025 mg/m ³
2,2'-dimorpholinyldiethyl ether CAS: 6425-39-4 EC: 229-194-7	Oral	Not relevant	Not relevant	0,5 mg/kg	Not relevant
	Dermal	Not relevant	Not relevant	0,5 mg/kg	Not relevant
	Inhalation	Not relevant	Not relevant	1,8 mg/m ³	Not relevant
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,05 mg/m ³	Not relevant	0,025 mg/m ³

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**
SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification		Short exposure		Long exposure	
		Systemic	Local	Systemic	Local
4,4'-Methylenediphenyl diisocyanate, oligomers CAS: 25686-28-6 EC: 500-040-3	Oral	Not relevant	Not relevant	Not relevant	Not relevant
	Dermal	Not relevant	Not relevant	Not relevant	Not relevant
	Inhalation	Not relevant	0,05 mg/m ³	Not relevant	0,025 mg/m ³

PNEC:



Identification				
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	STP	1 mg/L	Fresh water	1 mg/L
	Soil	1 mg/kg	Marine water	0,1 mg/L
	Intermittent	10 mg/L	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate CAS: Non-applicable EC: 905-806-4	STP	1 mg/L	Fresh water	1 mg/L
	Soil	1 mg/kg	Marine water	0,1 mg/L
	Intermittent	10 mg/L	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant
2,2'-dimorpholinyldiethyl ether CAS: 6425-39-4 EC: 229-194-7	STP	100 mg/L	Fresh water	0,1 mg/L
	Soil	1,58 mg/kg	Marine water	0,01 mg/L
	Intermittent	1 mg/L	Sediment (Fresh water)	8,2 mg/kg
	Oral	0,01 g/kg	Sediment (Marine water)	0,82 mg/kg
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	STP	1 mg/L	Fresh water	1 mg/L
	Soil	1 mg/kg	Marine water	0,1 mg/L
	Intermittent	10 mg/L	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant
4,4'-Methylenediphenyl diisocyanate, oligomers CAS: 25686-28-6 EC: 500-040-3	STP	1 mg/L	Fresh water	1 mg/L
	Soil	1 mg/kg	Marine water	0,1 mg/L
	Intermittent	10 mg/L	Sediment (Fresh water)	Not relevant
	Oral	Not relevant	Sediment (Marine water)	Not relevant

8.2 Exposure controls:
A.- Individual protection measures, such as personal protective equipment



In accordance with the order of importance to control professional exposure (Directive 98/24/EC) it is recommended to use localized extraction in the work area as a collective protection measure to avoid exceeding the occupational exposure limits. In case of using personal protective equipment it should have CE marking in accordance with Directive 2016/425/EC. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For additional information see subsection 7.1.

All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory respiratory tract protection	Filter mask for gases and vapours		EN 405:2002+A1:2010	Replace when there is a taste or smell of the contaminant inside the face mask. If the contaminant comes with warnings it is recommended to use isolation equipment.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory hand protection	Chemical protective gloves (Material: Nitrile, Breakthrough time: > 480 min, Thickness: 0.4 mm)		EN ISO 21420:2020	Replace the gloves at any sign of deterioration.



As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection





- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**



SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory face protection	Face shield		EN 166:2002 UNE-EN ISO 18526-1 al 4:2020 UNE-EN ISO 18526-1 al 4:2020 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
 Mandatory complete body protection	Disposable clothing for protection against chemical risks		EN 13034:2005+A1:2009 UNE-EN ISO 18526-1 al 4:2020 EN ISO 13982-1:2005/A1:2011 EN ISO 6529:2013 EN ISO 6530:2005 EN 464:1995	For professional use only. Clean periodically according to the manufacturer's instructions.
 Mandatory foot protection	Safety footwear for protection against chemical risk		EN ISO 20345:2022 EN 13832-1:2019	Replace boots at any sign of deterioration.

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
 Emergency shower	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	 Eyewash stations	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply):	0 % weight
V.O.C. density at 20 °C:	Not relevant
Average carbon number:	9,82
Average molecular weight:	364,05 g/mol

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:	Liquid
Appearance:	Not available
Colour:	 Brown
Odour:	Characteristic
Odour threshold:	Not relevant *

Volatility:

Boiling point at atmospheric pressure:	319 °C
Vapour pressure at 20 °C:	4 Pa
Vapour pressure at 50 °C:	26,78 Pa (0,03 kPa)
Evaporation rate at 20 °C:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Product description:

Density at 20 °C:	Not relevant *
Relative density at 20 °C:	1,05 - 1,15
Dynamic viscosity at 20 °C:	190 - 240 cP
Kinematic viscosity at 20 °C:	Not relevant *
Kinematic viscosity at 40 °C:	Not relevant *
Concentration:	Not relevant *
pH:	Not relevant *
Vapour density at 20 °C:	Not relevant *
Partition coefficient n-octanol/water 20 °C:	Not relevant *
Solubility in water at 20 °C:	Not relevant *
Solubility properties:	Not relevant *
Decomposition temperature:	Not relevant *
Melting point/freezing point:	Not relevant *

Flammability:

Flash Point:	Non Flammable (>60 °C)
Flammability (solid, gas):	Not relevant *
Autoignition temperature:	209 °C
Lower flammability limit:	Not relevant *
Upper flammability limit:	Not relevant *

Particle characteristics:

Median equivalent diameter:	Non-applicable
-----------------------------	----------------

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:	Not relevant *
Oxidising properties:	Not relevant *
Corrosive to metals:	Not relevant *
Heat of combustion:	Not relevant *
Aerosols-total percentage (by mass) of flammable components:	Not relevant *

Other safety characteristics:

Surface tension at 20 °C:	Not relevant *
Refraction index:	Not relevant *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7 from Safety Data Sheet.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Not applicable	Not applicable	Not applicable

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 10: STABILITY AND REACTIVITY (continued)

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others
Avoid strong acids	Not applicable	Not applicable	Not applicable	Avoid alkalis or strong bases

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for consumption. For more information see section 3
 - Corrosivity/Irritability: The consumption of a considerable dose can cause irritation in the throat, abdominal pain, nausea and vomiting.
- B- Inhalation (acute effect):
 - Acute toxicity : Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Corrosivity/Irritability: Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Produces skin inflammation.
 - Contact with the eyes: Produces eye damage after contact.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Exposure to this product can cause cancer. For more specific information on the possible health effects see section 2.
IARC: 4,4'-methylenediphenyl diisocyanate, isomers and homologues (3); 4,4'-methylenediphenyl diisocyanate (3)
 - Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Prolonged exposure can result in specific respiratory hypersensitivity.
 - Skin: Prolonged contact with the skin can result in episodes of allergic contact dermatitis.
- F- Specific target organ toxicity (STOT) - single exposure:

Causes irritation in respiratory passages, which is normally reversible and limited to the upper respiratory passages.
- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Exposure in high concentration can interfere with the central nervous system causing headache, dizziness, vertigo, nausea, vomiting, confusion, and in serious cases, loss of consciousness.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Not relevant

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Specific toxicology information on the substances:

Identification	Acute toxicity		Genus
	Route	Value	
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	LD50 oral	7616 mg/kg	Rat
	LD50 dermal	10000 mg/kg	Rabbit
	LC50 inhalation	11 mg/L (ATEI)	
2,2'-dimorpholinyl-diethyl ether CAS: 6425-39-4 EC: 229-194-7	LD50 oral	2025 mg/kg	Rat
	LD50 dermal	3038 mg/kg	Rabbit
	LC50 inhalation		
Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl) phenyl isocyanate CAS: Non-applicable EC: 905-806-4	LD50 oral		
	LD50 dermal		
	LC50 inhalation	11 mg/L (ATEI)	
4,4'-methylenediphenyl diisocyanate, isomers and homologues CAS: 9016-87-9 EC: 618-498-9	LD50 oral		
	LD50 dermal		
	LC50 inhalation	11 mg/L (ATEI)	

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product does not meet the criteria.

Other information

Not relevant

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

12.1 Toxicity:

Acute toxicity:

Identification	Concentration		Species	Genus
	Parameter	Value		
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	LC50	1000 mg/L (96 h)	Brachydanio rerio	Fish
	EC50	Not relevant		
	EC50	Not relevant		

Chronic toxicity:

Identification	Concentration		Species	Genus
	Parameter	Value		
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	NOEC	Not relevant		
	NOEC	10 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Not available

12.3 Bioaccumulative potential:

Substance-specific information:

Identification	Bioaccumulation potential	
	Parameter	Value
2,2'-dimorpholinyl-diethyl ether CAS: 6425-39-4 EC: 229-194-7	BCF	3
	Pow Log	
	Potential	Low
4,4'-methylenediphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	BCF	150
	Pow Log	4.51
	Potential	High

12.4 Mobility in soil:

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Absorption/desorption		Volatility	
2,2'-dimorpholinyl-diethyl ether CAS: 6425-39-4 EC: 229-194-7	Koc	786	Henry	2E-9 Pa·m ³ /mol
	Conclusion	Low	Dry soil	No
	Surface tension	Not relevant	Moist soil	No
4,4'-methylene-diphenyl diisocyanate CAS: 101-68-8 EC: 202-966-0	Koc	Not relevant	Henry	Not relevant
	Conclusion	Not relevant	Dry soil	Not relevant
	Surface tension	2,068E-2 N/m (283,45 °C)	Moist soil	Not relevant

12.5 Results of PBT and vPvB assessment:

Product does not meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product does not meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 04 09*	waste adhesives and sealants containing organic solvents or other hazardous substances	Hazardous

Type of waste (Regulation (EU) No 1357/2014):

HP5 Specific Target Organ Toxicity (STOT)/Aspiration Toxicity, HP6 Acute Toxicity, HP7 Carcinogenic, HP13 Sensitising, HP4 Irritant — skin irritation and eye damage

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-hazardous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

Transport of dangerous goods by land:

With regard to ADR 2023 and RID 2023:

- 14.1 UN number or ID number:** Not relevant
- 14.2 UN proper shipping name:** Not relevant
- 14.3 Transport hazard class(es):** Not relevant
- Labels: Not relevant
- 14.4 Packing group:** Not relevant
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
- Special regulations: Not relevant
- Tunnel restriction code: Not relevant
- Physico-Chemical properties: see section 9
- Limited quantities: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by sea:

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**

SECTION 14: TRANSPORT INFORMATION (continued)

With regard to IMDG 41-22:

- 14.1 UN number or ID number:** Not relevant
- 14.2 UN proper shipping name:** Not relevant
- 14.3 Transport hazard class(es):** Not relevant
Labels: Not relevant
- 14.4 Packing group:** Not relevant
- 14.5 Marine pollutant:** No
- 14.6 Special precautions for user**
Special regulations: Not relevant
EmS Codes:
Physico-Chemical properties: see section 9
Limited quantities: Not relevant
Segregation group: Not relevant
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

Transport of dangerous goods by air:

With regard to IATA/ICAO 2024:

- 14.1 UN number or ID number:** Not relevant
- 14.2 UN proper shipping name:** Not relevant
- 14.3 Transport hazard class(es):** Not relevant
Labels: Not relevant
- 14.4 Packing group:** Not relevant
- 14.5 Environmental hazards:** No
- 14.6 Special precautions for user**
Physico-Chemical properties: see section 9
- 14.7 Maritime transport in bulk according to IMO instruments:** Not relevant

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- Article 95, REGULATION (EU) No 528/2012: Not relevant
- Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Not relevant
- Regulation (EU) No 2024/590, about substances that deplete the ozone layer: Not relevant
- REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Not relevant
- Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Not relevant

Seveso III:

Not relevant

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10**
SECTION 15: REGULATORY INFORMATION (continued)

Contains more than 0.1 % of 4,4'-methylenediphenyl diisocyanate, isomers and homologues, 4,4'-methylenediphenyl diisocyanate, Reaction mass of 4,4'-methylenediphenyl diisocyanate and o-(p-isocyanatobenzyl)phenyl isocyanate, 4,4'-Methylenediphenyl diisocyanate, oligomers by weight. 1. Shall not be used as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 August 2023, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the employer or self-employed ensures that industrial or professional user(s) have successfully completed training on the safe use of diisocyanates prior to the use of the substance(s) or mixture(s).

2. Shall not be placed on the market as substances on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) after 24 February 2022, unless:

(a) the concentration of diisocyanates individually and in combination is less than 0,1 % by weight, or (b) the supplier ensures that the recipient of the substance(s) or mixture(s) is provided with information on the requirements referred to in point (b) of paragraph 1 and the following statement is placed on the packaging, in a manner that is visibly distinct from the rest of the label information: "As from 24 August 2023 adequate training is required before industrial or professional use".

3. For the purpose of this entry "industrial and professional user(s)" means any worker or self-employed worker handling diisocyanates on their own, as a constituent in other substances or in mixtures for industrial and professional use(s) or supervising these tasks.

4. The training referred to in point (b) of paragraph 1 shall include the instructions for the control of dermal and inhalation exposure to diisocyanates at the workplace without prejudice to any national occupational exposure limit value or other appropriate risk management measures at national level. Such training shall be conducted by an expert on occupational safety and health with competence acquired by relevant vocational training. That training shall cover as a minimum:

(a) the training elements in point (a) of paragraph 5 for all industrial and professional use(s).

(b) the training elements in points (a) and (b) of paragraph 5 for the following uses:

- handling open mixtures at ambient temperature (including foam tunnels)
- spraying in a ventilated booth
- application by roller
- application by brush
- application by dipping and pouring
- mechanical post treatment (e.g. cutting) of not fully cured articles which are not warm anymore
- cleaning and waste
- any other uses with similar exposure through the dermal and/or inhalation route

(c) the training elements in points (a), (b) and (c) of paragraph 5 for the following uses:

- handling incompletely cured articles (e.g. freshly cured, still warm)
- foundry applications
- maintenance and repair that needs access to equipment
- open handling of warm or hot formulations (> 45 °C)
- spraying in open air, with limited or only natural ventilation (includes large industry working halls) and spraying with high energy (e.g. foams, elastomers)
- and any other uses with similar exposure through the dermal and/or inhalation route.

5. Training elements:

(a) general training, including on-line training, on:

- chemistry of diisocyanates
- toxicity hazards (including acute toxicity)
- exposure to diisocyanates
- occupational exposure limit values
- how sensitisation can develop
- odour as indication of hazard
- importance of volatility for risk
- viscosity, temperature, and molecular weight of diisocyanates
- personal hygiene
- personal protective equipment needed, including practical instructions for its correct use and its limitations
- risk of dermal contact and inhalation exposure
- risk in relation to application process used
- skin and inhalation protection scheme
- ventilation
- cleaning, leakages, maintenance
- discarding empty packaging
- protection of bystanders
- identification of critical handling stages
- specific national code systems (if applicable)
- behaviour-based safety
- certification or documented proof that training has been successfully completed

(b) intermediate level training, including on-line training, on:

- additional behaviour-based aspects
- maintenance

- CONTINUED ON NEXT PAGE -

SECTION 15: REGULATORY INFORMATION (continued)

- management of change
 - evaluation of existing safety instructions
 - risk in relation to application process used
 - certification or documented proof that training has been successfully completed
- (c) advanced training, including on-line training, on:
- any additional certification needed for the specific uses covered
 - spraying outside a spraying booth
 - open handling of hot or warm formulations (> 45 °C)
 - certification or documented proof that training has been successfully completed
6. The training shall comply with the provisions set by the Member State in which the industrial or professional user(s) operate. Member States may implement or continue to apply their own national requirements for the use of the substance(s) or mixture(s), as long as the minimum requirements set out in paragraphs 4 and 5 are met.
7. The supplier referred to in point (b) of paragraph 2 shall ensure that the recipient is provided with training material and courses pursuant to paragraphs 4 and 5 in the official language(s) of the Member State(s) where the substance(s) or mixture(s) are supplied. The training shall take into consideration the specificity of the products supplied, including composition, packaging, and design.
8. The employer or self-employed shall document the successful completion of the training referred to in paragraphs 4 and 5. The training shall be renewed at least every five years.
9. Member States shall include in their reports pursuant to Article 117(1) the following information:
- (a) any established training requirements and other risk management measures related to the industrial and professional uses of diisocyanates foreseen in national law
- (b) the number of cases of reported and recognised occupational asthma and occupational respiratory and dermal diseases in relation to diisocyanates
- (c) national exposure limits for diisocyanates, if there are any
- (d) information about enforcement activities related to this restriction.
10. This restriction shall apply without prejudice to other Union legislation on the protection of safety and health of workers at the workplace.
- Contains more than 0.1 % of 4,4'-methylenediphenyl diisocyanate, 4,4'-methylenebisphenyl diisocyanate, isomers and homologues, 4,4'-Methylenediphenyl diisocyanate, oligomers by weight. This product may not be distributed in its present form for first-time sale to the general public after 27th December 2010 unless the packaging contains protective gloves meeting the provisions of Regulation (EU) 2016/425.
- Shall not be used in:
- ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
 - tricks and jokes,
 - games for one or more participants, or any article intended to be used as such, even with ornamental aspects.
- Contains Octamethylcyclotetrasiloxane, Decamethylcyclopentasiloxane, Dodecamethylcyclohexasiloxane. 1. Shall not be placed on the market (a) as a substance on its own; (b) as a constituent of other substances; or (c) in mixtures; in a concentration equal to or greater than 0,1 % by weight of the respective substance after 6 June 2026. 2. Shall not be used as a solvent for the dry cleaning of textiles, leather and fur after 6 June 2026. 3. By way of derogation: (a) for D4 and D5 in wash-off cosmetic products, paragraph 1, point (c), shall apply after 31 January 2020. For the purposes of this point, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1), point (a), of Regulation (EC) No 1223/2009 of the European Parliament and of the Council (*) that, under normal conditions of use, are washed off with water after application; (b) for all cosmetic products other than the ones mentioned in paragraph 3(a), paragraph 1 shall apply after 6 June 2027; (c) for devices as defined in Article 1(4) of Regulation (EU) 2017/745 of the European Parliament and of the Council (**) and in Article 1(2) of Regulation (EU) 2017/746 of the European Parliament and of the Council (***) , paragraph 1 shall apply after 6 June 2031; (d) for medicinal products, as defined in Article 1, point 2, of Directive 2001/83/EC, and for veterinary medicinal products, as defined in Article 4(1) of Regulation (EU) 2019/6 (****), paragraph 1 shall apply after 6 June 2031; (e) for D5 as a solvent in the dry cleaning of textiles, leather and fur, paragraphs 1 and 2 shall apply after 6 June 2034. 4. By way of derogation, paragraph 1 shall not apply to the: (a) placing on the market of D4, D5 and D6 for the following industrial uses: — as a monomer in the production of silicone polymer, — as an intermediate in the production of other silicon substances, — as a monomer in polymerisation, — in the formulation or (re)packing of mixtures, — in the production of articles, — in non-metal surface treatment; (b) placing on the market of D5 and D6 for use as devices, as defined in Article 1(4) of Regulation (EU) 2017/745, for the treatment and care of scars and wounds, the prevention of wounds and the care of stoma; (c) placing on the market of D5 for professional use in the cleaning or restoration of art and antiques; (d) placing on the market of D4, D5 and D6 for use as laboratory reagent in research and development activities carried out under controlled conditions. 5. By way of derogation, paragraph 1, point (b), shall not apply to the placing on the market of D4, D5 and D6: — as a constituent of a silicone polymer on its own, — as a constituent of a silicone polymer in a mixture derogated under paragraph 6. 6. By way of derogation, paragraph 1, point (c), shall not apply to the placing on the market of mixtures that contain D4, D5 or D6 as residues from silicone polymers, under the following conditions: (a) D4, D5 or D6 in a concentration equal to or less than 1 % by weight of the respective substance in the mixture, for use in adhesion, sealing, gluing and casting; (b) D4 in a concentration equal to or less than 0,5 % by weight, or D5 or D6 in a concentration equal to or less than 0,3 % by weight of either substance in the mixture for use as protective coatings (including marine coatings); (c) D4, D5 or D6 in a concentration equal to or less than 0,2 % by weight of the respective substance in the mixture, for use as devices as defined in Article 1(4) of Regulation (EU) 2017/745 and in Article 1(2) of Regulation (EU) 2017/746, other than the devices referred to in paragraph 6(d); (d) D5 in a concentration equal to or less than 0,3 % by weight

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10****SECTION 15: REGULATORY INFORMATION (continued)**

in the mixture or D6 in a concentration equal to or less than 1 % by weight in the mixture, for use as devices as defined in Article 1(4) of Regulation (EU) 2017/745, for dental impression; (e) D4 in a concentration equal to or less than 0,2 % by weight in the mixture, or D5 or D6 in a concentration equal to or less than 1 % by weight of either substance in the mixture for use as silicone insoles for horses, or as horseshoes; (f) D4, D5 or D6 in a concentration equal to or less than 0,5 % by weight of the respective substance in the mixture, for use as adhesion promoters; (g) D4, D5 or D6 in a concentration equal to or less than 1 % by weight of the respective substance in the mixture, for use in 3D-printing; (h) D5 in a concentration equal to or less than 1 % by weight in the mixture or D6 in a concentration equal to or less than 3 % by weight in the mixture, for rapid prototyping and mould making, or high performance uses stabilised by quartz filler; (i) D5 or D6 in a concentration equal to or less than 1 % by weight of either substance in the mixture, for use in pad printing, or manufacturing of printing pads; (j) D6 in a concentration equal to or less than 1 % by weight of the mixture, for professional use in the cleaning or restoration of art and antiques. 7. By way of derogation, paragraphs 1 and 2 shall not apply to the placing on the market for use, or to the use, of D5 as a solvent in strictly controlled closed dry cleaning systems for textile, leather and fur, where the cleaning solvent is recycled or incinerated.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION**Legislation related to safety data sheets:**

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

Not relevant

Texts of the legislative phrases mentioned in section 2:

H315: Causes skin irritation.

H334: May cause allergy or asthma symptoms or breathing difficulties if inhaled.

H317: May cause an allergic skin reaction.

H351: Suspected of causing cancer.

H335: May cause respiratory irritation.

H373: May cause damage to organs through prolonged or repeated exposure (Inhalation).

H373: May cause damage to organs through prolonged or repeated exposure.

H332: Harmful if inhaled.

H319: Causes serious eye irritation.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

Acute Tox. 4: H332 - Harmful if inhaled.

Carc. 2: H351 - Suspected of causing cancer.

Eye Irrit. 2: H319 - Causes serious eye irritation.

Resp. Sens. 1: H334 - May cause allergy or asthma symptoms or breathing difficulties if inhaled.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction.

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure (Inhalation).

STOT RE 2: H373 - May cause damage to organs through prolonged or repeated exposure.

STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

- CONTINUED ON NEXT PAGE -

**TEKINJECT PU 1C FAST FLEX
PU-10****SECTION 16: OTHER INFORMATION (continued)**

Skin Irrit. 2: Calculation method
Resp. Sens. 1: Calculation method
Skin Sens. 1: Calculation method
Carc. 2: Calculation method
STOT SE 3: Calculation method
STOT RE 2: Calculation method
STOT RE 2: Calculation method
Acute Tox. 4: Calculation method
Eye Irrit. 2: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

<http://echa.europa.eu>
<http://eur-lex.europa.eu>

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road
IMDG: International maritime dangerous goods code
IATA: International Air Transport Association
ICAO: International Civil Aviation Organisation
COD: Chemical Oxygen Demand
BOD5: 5day biochemical oxygen demand
BCF: Bioconcentration factor
LD50: Lethal Dose 50
LC50: Lethal Concentration 50
EC50: Effective concentration 50
LogPOW: Octanolwater partition coefficient
Koc: Partition coefficient of organic carbon
UFI: unique formula identifier
IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

- END OF SAFETY DATA SHEET -